


TTH



Plug for general purpose use in hard and soft insulation pads. **Special plug used for fixation of isolation material.** Plug is easily installed only by hammering in. **High resistant in meteorological conditions.**

INSTALLATION:

**APPLICATION**

- > hollow brick
- > brick
- > concrete
- > stone

**MATERIAL**

Plug – Copolymer
Nail – Polyamide
(Nylon) with glass fibre

**ADVANTAGES**

- > fast installation
- > easy installation
- > low price
- > no thermal bridge

TECHNICAL DATA:

Size	Drill \varnothing	Minimal drill depth	Fixing depth	Anchor lenght	Disc \varnothing	Insulation thickness	Recommended loads	
							concrete	brick
10/60-90	10	45	40	90	60	40	0,187	0,150
10/60-110	10	45	40	110	60	60	0,187	0,150
10/60-120	10	45	40	120	60	70	0,187	0,150
10/60-130	10	45	40	130	60	80	0,187	0,150
10/60-140	10	45	40	140	60	90	0,187	0,150
10/60-150	10	45	40	150	60	100	0,187	0,150
10/60-160	10	45	40	160	60	110	0,187	0,150
10/60-170	10	45	40	170	60	120	0,187	0,150
10/60-180	10	45	40	180	60	130	0,187	0,150
10/60-190	10	45	40	190	60	140	0,187	0,150
10/60-210	10	45	40	210	60	160	0,187	0,150

All figures are in mm

Recommended loads in kN (1 kN = 100 Kg)

**TRUHLÁŘ** a spol., s.r.o.

Hlavní 812, 251 68 Hlubočinka, Czech Republic | tel.: +420 323 671 745 | fax: +420 323 671 744 | e-mail: export@ttt.cz