


# UPP



Lightweight all-purpose fixing for professional and DIY use. High quality Polypropylene for optimal performance and easy application. Thermal resistance from  $-20\text{ }^{\circ}\text{C}$  to  $+80\text{ }^{\circ}\text{C}$ . Recommended application temperature from  $-5\text{ }^{\circ}\text{C}$ .

INSTALLATION:



## APPLICATION

- › concrete
- › brick
- › natural stone
- › sand-stone



## MATERIAL

Polypropylene



## ADVANTAGES

- › wide area of application
- › high temperature resistance
- › low price

## TECHNICAL DATA:

Size	Drill $\varnothing$	Minimal drill depth	Anchor length	Screw $\varnothing$	Recommended loads (concrete)
5x25	5	30	25	2,5-4	0,26
6x30	6	35	30	3,5-5	0,42
8x40	8	45	40	4,5-6	0,60
10x50	10	55	50	6-8	0,74
10x60	10	65	60	6-8	0,74
12x60	12	65	60	8-10	1,06
14x75	14	80	75	10-12	1,41
16x90	16	95	90	12	2,32
16x100	16	105	100	12	2,32
16x120	16	125	120	12	2,32
16x140	16	145	140	12	2,32

All figures are in mm

Recommended loads in kN (1 kN  $\approx$  100 Kg)

STANDARD PLUGS

UPP

TRUHLÁŘ a spol., s.r.o.

Hlavní 812, 251 68 Hlubočinka, Czech Republic | tel.: +420 323 671 745 | fax: +420 323 671 744 | e-mail: export@ttt.cz

