


Frame plugs with screws RMS, RMP, RMT



The RM plug has long expansion area and is suitable for through – fixing into cavity bricks etc. The special internal design, the long expansion area, provides secure fixing into concrete, stone and softer material such as bricks and low density block work.

RM plugs are available in sets with hexagon, pozidrive and torx head.


Application:

- hollow brick
- brick
- concrete
- stone

Advantages:

- strong anchoring
- high temperature resistance
- easy installation
- complete package

Installation



Material: Polyamide PA6 (Nylon)

Type RMS, RMP and RMT – Technical data and price

Size	Drill Ø	Minimal drill depth	Anchor length	Screw Ø	Fixable thickness	Recommended loads	Basic price / 100 pcs	
							RMS	RMT, RMP
8 x 60	8	70	60	5 - 5,5	5	0,75	8,30 €	7,47 €
8 x 80	8	90	80	5 - 5,5	25	0,75	9,97 €	8,97 €
8 x 100	8	110	100	5 - 5,5	45	0,75	12,30 €	11,13 €
8 x 120	8	130	120	5 - 5,5	65	0,75	15,63 €	14,13 €
8 x 140	8	150	140	5 - 5,5	85	0,75	17,97 €	16,30 €
8 x 160	8	170	160	5 - 5,5	105	0,75	22,30 €	20,30 €
10 x 80	10	90	80	6 - 7	15	0,92	16,13 €	14,63 €
10 x 100	10	110	100	6 - 7	35	0,92	18,13 €	16,63 €
10 x 120	10	130	120	6 - 7	55	0,92	21,80 €	19,97 €
10 x 140	10	150	140	6 - 7	75	0,92	26,13 €	23,97 €
10 x 160	10	170	160	6 - 7	95	0,92	33,30 €	30,63 €

All figures are in mm

Recommended loads in kN
(1 kN \approx 100 Kg)